

Spirit Soul Rigid Click 55.

Technical data.


	contains	m ²	gross weight
1 pack Spirit Soul Rigid Click 55 planks	6 planks	2,08 m ²	21,63 kg
1 pallet Spirit Soul Rigid Click 55 planks (incl. pallet)	39 packs	81,31 m ²	869,57 kg
1 pack Spirit Soul Rigid Click 55 tiles	4 tiles	1,67 m ²	17,44 kg
1 pallet Spirit Soul Rigid Click 55 tiles (incl. pallet)	50 packs	83,61 m ²	900,10 kg
1 pack Spirit Soul Rigid Click 55 herringbone	30 planks	1,97 m ²	20,63 kg
1 pallet Spirit Soul Rigid Click 55 herringbone (incl. pallet)	42 packs	82,92 m ²	891,46 kg

product specifications

norm	Spirit Soul Rigid Click 55 Planks	Spirit Soul Rigid Click 55 Tiles	Spirit Soul Rigid Click 55 Herringbone	
Dimensions	EN ISO 24342	L 1524 x W 228 mm	L 914,4 x W 457,2 mm	L 609,6 x W 107,95 mm
Wear layer	EN ISO 24340	0,55 mm	0,55 mm	0,55 mm
Embossing		embossed in register (EIR)	stone embossed	wood embossed in register (EIR) & stone embossed
Total thickness	EN ISO 24346	6 mm (5 + 1)	6 mm (5 + 1)	6 mm (5 + 1)
Integrated underlay		yes (1 mm)	yes (1 mm)	yes (1 mm)
Locking system				
Bevel type		micro V4	micro V4	micro V4
Usage classification	EN ISO 16511	23/33	23/33	23/33
Residential warranty		lifetime	lifetime	lifetime
Commercial warranty		10 years	10 years	10 years

test results

norm	results	
Underfloor heating	EN ISO 12524	suitable
Castor chair	EN ISO 4918	pass
Fire resistance	EN 13501-1	Bfl-s1
Chemical resistance	EN ISO 26987	OK
Residual indentation	EN ISO 24343-1	≤ 0,10 mm – pass
Thermal resistance	ISO 8302	0,030 m ² K/W
Scratch resistance	EN 16094	MSR-A1/B1
Slip resistance	DIN 51130	R10
	EN ISO 13893	class DS
Pendulum slip resistance (PTV)	EN 16165	36+
Sound reduction: impact sound	EN ISO 10140-3 EN ISO 717-2	20 dB
Dimensional stability	EN ISO 23999	≤ 0,15 % - pass
Lock strength	EN ISO 16511	> 1,5 kN/m – pass
Light fastness	EN ISO 105-B02	≥ 6 - pass
Static electrical propensity	EN 1815	antistatic (≤ 2 kV)



vinyl planks & tiles.

Spirit Soul Rigid Click 55.

Technical data.

composition



- 1 Protective PU coating/lacquer*
- 2 Wear layer 0,55 mm
- 3 Decor layer
- 4 Rigid board with 5G locking system
- 5 Integrated IXPE underlay 1 mm

*for wood products enhanced with the UltraShield Matt technology™ that gives an ultra matt look, ultra scratch resistance & ultra slip resistance

Spirit Soul Glue Down 55.

Technical data.


	contains	m ²	gross weight
1 pack Spirit Soul Glue Down 55 planks	10 planks	3,45 m ²	16,49 kg
1 pallet Spirit Soul Glue Down 55 planks (incl. pallet)	51 packs	175,95 m ²	866,94 kg
1 pack Spirit Soul Glue Down 55 tiles	10 tiles	4,18 m ²	19,14 kg
1 pallet Spirit Soul Glue Down 55 tiles (incl. pallet)	46 packs	192,31 m ²	908,53 kg
1 pack Spirit Soul Glue Down 55 herringbone	64 planks	4,46 m ²	19,86 kg
1 pallet Spirit Soul Glue Down 55 herringbone (incl. pallet)	42 packs	187,29 m ²	859,20 kg

product specifications

	norm	Spirit Soul Glue Down 55 Planks	Spirit Soul Glue Down 55 Tiles	Spirit Soul Glue Down 55 Herringbone
Dimensions	EN ISO 24342	L 1500 x W 230 mm	L 914,4 x W 457,2 mm	L 609,6 x W 114,3 mm
Wear layer	EN ISO 24340	0,55 mm	0,55 mm	0,55 mm
Embossing		embossed in register (EIR)	stone embossed	wood embossed in register (EIR) & stone embossed
Total thickness	EN ISO 24346	2,5 mm	2,5 mm	2,5 mm
Integrated underlay		no	no	no
Locking system		no	no	no
Bevel type		micro V4	micro V4	micro V4
Usage classification	EN ISO 10582	23/33/42	23/33/42	23/33/42
Residential warranty		lifetime	lifetime	lifetime
Commercial warranty		10 years	10 years	10 years

test results

	norm	results
Underfloor heating	EN ISO 12524	suitable
Castor chair	EN ISO 4918	pass
Fire resistance	EN 13501-1	Bfl-s1
Chemical resistance	EN ISO 26987	OK
Residual indentation	EN ISO 24343-1	≤ 0,10 mm – pass
Thermal resistance	ISO 8302	0,010 m ² K/W
Scratch resistance	EN 16094	MSR-A1/B1
Slip resistance	DIN 51130	R10
	EN ISO 13893	class DS
Pendulum slip resistance (PTV)	EN 16165	36+
Sound reduction: impact sound	EN ISO 10140-3 EN ISO 717-2	2 dB
Dimensional stability	EN ISO 23999	≤ 0,15 % - pass
Light fastness	EN ISO 105-B02	≥ 6 - pass
Static electrical propensity	EN 1815	antistatic (≤ 2 kV)



vinyl planks & tiles.

Spirit Soul Glue Down 55.

Technical data.

composition



- 1 Protective PU coating/lacquer*
- 2 Wear layer 0,55 mm
- 3 Decor layer
- 4 PVC backing layer

*for wood products enhanced with the UltraShield Matt technology™ that gives an ultra matt look, ultra scratch resistance & ultra slip resistance