

Collection Rigid Floors Click

NUANCES
UNIKALO
partenaire du peintre



Grey

A14380



EN STOCK

Collection Rigid Floors Click

NUANCES
UNIKALO
partenaire du peintre



Invisible

A14379



EN STOCK

Collection Rigid Floors Click

NUANCES
UNIKALO
partenaire du peintre



Natural

A14378



EN STOCK

Collection Rigid Floors Click

NUANCES
UNIKALO
partenaire du peintre



Oak

A16050



EN STOCK

Collection Rigid Floors Click

Fume

A16593



@Rigid Floors



EN STOCK

Collection Rigid Floors Click

Fiche technique

	STANDARD	RESULT
Dimensions and basic data		
 SIZE	EN ISO 24342	Plank: 180 x 1220 mm
 THICKNESS	EN ISO 24346	5.0 mm (4.0 mm spc + 1 mm integrated backing)
 WEAR LAYER	EN ISO 24340	0.55 mm
LOCKING METHOD		Click-system
SURFACE TREATMENT		PU coating + protected with aluminium oxide (anti-scratch) and stain resistant technology.
CORE		Sound reducing water resistant rigid core, SPC
Technical data - CE EN 14041		
 BEVELLED EDGE	MICRO	4 Sides
 MASS		10.80 kg/m ²
 STANDARDS	EN 16511	
 REACTION TO FIRE	EN 685 / EN ISO 10874 - Commercial	33: Commercial heavy
 REACTION TO FIRE	EN 685 / EN ISO 10874 - Domestic	23: Domestic heavy
 REACTION TO FIRE	EN 13501-1	Bfl-S1
 STAINING RESISTANCE	EN 438-2	Group 1/2/3: Degree 5
 LIGHT FASTNESS	EN ISO 105-B02	> 6
 DIMENSIONAL STABILITY	EN 434 / EN ISO 23999	≤ 0.10 %
 ACOUSTIC IMPACT - NOISE REDUCTION	EN ISO 717-2/ EN ISO 140-8	ΔL _w = 23 DB
 ELECTRICAL BEHAVIOR - BODY VOLTAGE	EN 1815	Pass
 INDENTATION - RESIDUAL	EN ISO 24343-1	≤ 0.10 mm
 CASTOR CHAIR	ISO 4918	Pass
 THERMAL RESISTANCE	EN 12667	<0.122 (m ² K/W)
 SLIP RESISTANCE*	EN 13893/ DIN 51130	DS R9
WEAR RESISTANCE	EN 660-2/ EN 649	Class T
 IMPACT RESISTANCE	EN 13329	Pass
CLICK TENSION	ISO 24334	Short side: 14.7 kn/m - Long side: 3.7 kn/m
 SWELLING	ISO 24336	Pass
 FLOOR HEATING	Appropriate for standard heating systems in cement flooring.	Not appropriate for heating electric films.
Dangerous substances		
 VOC EMISSION	French/Belgian/ German Regulations	Pass
 FORMALDEHYDE EMISSION	EN 1717-1	E1
REACH		Friendly reach compliant
 PCP	EN 12673	Pass